ProLite E2002WS-1



This incredible value for money 20" Wide Screen is aimed at the user who appreciates the higher 1680x1050 screen resolution but lacks space for a 22”. Its 5msec response time and 5000:1 contrast ratio (DCR) ensures against dissapointment when watching video or playing the latest fast action game on your PC. The ProLite E2002WS has both one D-Sub and one DVI input and is available in black.

Panel	TN
Diagonal	20"
Display area h x w	270.9 x 433.4 mm
Response time	5 ms
Contrast ratio	1000 : 1 typical
Contrast ratio	5000 : 1 DCR
Brightness	300 cd/m² typical
Viewing zone	horizontal/vertical: 160°/160°; right/left: 80°/80°; up/down: 80/80°
Display colour	16.7 million
Pixel pitch h x v	0.258 x 0.258 mm
Native resolution	1680 x 1050 (1.8 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D cable, audio cable, user manual, stand, cable holder
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 6 languages (EN, DE, FR, ES, IT, JP) and 6 front controls (Power, Menu, + Button, - Button, Auto, Input)
User controls	brightness, contrast, clock, phase, V-position, H-position, auto adjust, colour temperature, sharpness, gamma, economy mode, OSD position, OSD time off, OSD language, picture mode, volume, signal select, full screen, DCR, reset
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TÜV-Ergonomics
Safety	TÜV GS, CE, VCCI-B
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	42 W typical; max. 2 W in Power management mode
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	472.5 x 383.5 x 210 mm
Weight	4.5 kg
Aspect ratio	16 : 10

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.